

CLEANGUARD Extinguishers



CLEANGUARD Clean-Agent Extinguishers are designed for protection of light and ordinary hazards. These compact and portable extinguishers are suited for compliance, commercial fire protection needs. Typical applications include:

- Computer rooms
- Essential communication areas
- Irreplaceable data, document, and art storage rooms
- Laboratories
- Sensitive/expensive equipment
- NM unit is MR Conditional for areas such as MRI rooms
- UL/ULC Approved and Listed
- FE05S, FE09, FE13 models FAA approved
- Six-year limited warranty (see ansul.com for details)



Model	FE02VB	FE05S	FE09	FE13	FE13NM
Extinguisher Part No. UL	429107	442255	429021	429022	432893
Extinguisher Part No. ULC	429596	442256	429598	429599	433214
Bracket Part No.	24610 (Included)	429146	422737	30937	—
Agent Capacity	2.5 lb (1.1 kg)	4.75 lb (2.2 kg)	9.5 lb (4.3 kg)	13.25 lb (6 kg)	13.25 lb (6 kg)
UL/ULC Rating	2-B:C	5-B:C	1-A:10-B:C	2-A:10-B:C	1-A:10-B:C
Discharge Time	9.0 sec	8.5 sec	9.5 sec	13.5 sec	13.5 sec
Agent Flow Rate (per sec)	0.30 lb (0.14 kg)	0.60 lb (0.27 kg)	1.15 lb (0.52 kg)	1.12 lb (0.51 kg)	1.12 lb (0.51 kg)
Charged Weight	5.0 lb (2.3 kg)	9.5 lb (4.3 kg)	21.81 lb (4.65 kg)	25.63 lb (11.63 kg)	20.0 lb (9.1 kg)
Dimensions:					
Height: in. (mm)	14 1/4 (362)	16 3/4 (425)	18 3/4 (476)	22 1/2 (572)	25 1/2 (648)
Width: in. (mm)	5 3/4 (146)	8 1/2 (216)	9 (229)	9 1/2 (241)	9 (229)
Depth: in. (mm)	3 3/8 (86)	4 7/16 (113)	7 (178)	7 (178)	7 (178)



C.F.H. SÉCURITÉ INC.

1455 Boul. Pitfield • Ville St-Laurent, P.Q. H4S 1G3 • (514) 333-3389 • Fax : (514) 333-1887 • www.cfhsecurite.com