



Model	WM250
Part #	51000 (51000 ULC)
Cylinder/Valve Material	Stainless Steel/Plated Brass
Agent Capacity	2.5 gallons (9.6 liters)
UL/ULC Rating	2-A:C
Temperature Range	40° to 120°F (4.4° to 49°C)
Discharge Time	73 sec
Discharge Range	5 to 10 ft. (1.5 to 3m)
Operating Pressure	100 psi (689 kPa)
Mounting Type	Wall
USCG Approval	N/A
Ship Weight	Full: 30.25 lb. (13.7 kg)
Unit Height	28 in (78.1 cm)
Unit Width (Incl. Hose)	14 in (35.6 cm)
Unit Diameter	7 in (17.8 cm)

## **WATER MIST**

The Water Mist unit uses deionized water and incorporates a unique spray nozzle. These features make it safe for use on energized electrical equipment. Water Mist is considered to be the #1 extinguisher choice for libraries and hospitals.

Water extinguishers are suitable for use on Class A fires. Water Mist is suitable for use on both Class A and Class C fires.

Typical Uses: For common combustible fires in offices, classrooms, churches, parking garages, and hotel/motel assembly halls and guest areas. For common combustible fires in businesses such as retail stores, light manufacturing facilities, research facilities, auto dealerships, vehicle/aircraft/marine service centers, and manufacturing processes such as painting, dipping, and coating.

Third Party Approvals For Peace Of Mind









