

SENTRY Dry Chemical Extinguishers

Model	A02S A02SVB*	AA05S-1 AA05SVB-1*	A05S A05SVB*	PK05S	AA10S CR-AA10SI	PK10S CR-PK10SI	C10S	AA20-1 CR-AA20I-1	PK20 CR-PK20I	C20
Extinguisher Part No. UL	438732 438735	442257 442258	442235 442236	442253	436500 436583	436494 436586	436497	434747 434750	429011 429012	429017
Extinguisher Part No. ULC	438946 438738	442260 442261	442238 442239	—	436509 —	436791 —	—	434765 —	434276 —	—
International** Part No. UL	— 442656	442286 442297	442278 442280	442301 —	442662 —	442663 —	—	442664 —	442665 —	—
Arabic Part No.	— 438747	—	442237 —	—	436506 —	—	—	434810 —	430891 —	—
Bracket Part No.	24610	429146	429146	429146	435793	435793	435793	30937	30937	30937
Agent	FORAY	FORAY	FORAY	Purple-K	FORAY	Purple-K	PLUS-FIFTY C	FORAY	Purple-K	PLUS-FIFTY C
Agent Capacity	2 1/2 lb (1.13 kg)	5 lb (2.27 kg)	5 lb (2.27 kg)	5 lb (2.27 kg)	10 lb (4.54 kg)	10 lb (4.54 kg)	10 lb (4.54 kg)	20 lb (9.07 kg)	20 lb (9.07 kg)	20 lb (9.07 kg)
UL/ULC Rating	1-A: 10-B:C	3-A: 40-B:C	3-A: 10-B:C	60-B:C	4-A: 80-B:C	80-B:C	60-B:C	10-A: 120-B:C	120-B:C	80-B:C
Discharge Time	9 sec	14 sec	15 sec	17 sec	21 sec	22 sec	19 sec	28 sec	30 sec	21 sec
Agent Flow Rate lb/sec (kg/sec)	0.31 (0.14)	0.38 (0.17)	0.34 (0.15)	0.30 (0.14)	0.52 (0.24)	0.52 (0.24)	0.46 (0.21)	0.59 (0.27)	0.73 (0.33)	0.67 (0.30)
Charged Weight (with agent)	5 lb (2.27 kg)	9 lb, 14 oz (4.15 kg)	9 lb, 14 oz (4.15 kg)	9 lb, 14 oz (4.15 kg)	17 lb, 0 oz (7.73 kg)	17 lb, 0 oz (7.73 kg)	17 lb, 0 oz (7.73 kg)	32 lb, 2 oz (14.60 kg)	32 lb, 2 oz (14.60 kg)	32 lb, 2 oz (14.60 kg)
Dimensions:										
Height: in. (mm)	14 1/4 (362)	16 3/4 (425)	16 3/4 (425)	16 3/4 (425)	20 1/2 (520)	20 1/2 (520)	20 1/2 (520)	22 1/2 (572)	22 1/2 (572)	22 1/2 (572)
Width: in. (mm)	5 1/2 (140)	8 1/2 (216)	8 1/2 (216)	8 1/2 (216)	8 1/4 (210)	8 1/4 (210)	8 1/4 (210)	9 1/2 (241)	9 1/2 (241)	9 1/2 (241)
Depth: in. (mm)	3 3/8 (86)	4 7/16 (113)	4 7/16 (113)	4 7/16 (113)	5 1/4 (135)	5 1/4 (135)	5 1/4 (135)	7 7/32 (183)	7 7/32 (183)	7 7/32 (183)

*VB: Includes Vehicle Bracket

**Products to be used outside of the Americas to comply with GHS labeling requirements.

LEGEND (Prefix):

A FORAY Dry Chemical
AA FORAY Industrial Grade Dry Chemical
AA (-1) FORAY Modified Technical Grade Dry Chemical
PK Purple-K Dry Chemical
C PLUS-FIFTY C Dry Chemical
I Industrial (Corrosion Resistant)

C.F.H. SÉCURITÉ INC.

1455 Boul. Pitfield • Ville St-Laurent, P.Q. H4S 1G3 • (514) 333-3389 • Fax : (514) 333-1887 • www.cfhsecurite.com